















1	Class.forName() make the driver class available
2	<pre>String url = "jdbc:odbc:supplier-part";</pre>
	This is the connect string. The connect string, mentions the driver as well as the database. For the example above, the driver is the jdbc:odbc bridge driver. The database is supplier-part.
3	<pre>Connection con=DriverManager.getConnection(url, uID, pw);</pre>
	Get a connection (session) with a specific database. Within the context of a Connection, SQL statements are executed and results are returned.
	A Connection can be used to obtain information about the DB By default a Connection automatically <i>commits</i> changes after each statement.
	Typically, setting up a connection is an expennsive operation.



```
Example:
Statement stmt = con.createStatement();
// Send the query to the DB, get back a ResultSet
ResultSet rs = stmt.executeQuery("SELECT * FROM PART;");
// Go through all rows returned by the query
while(rs.next()){
// Pull out individual columns from the current row
int pno=rs.getInt("PNO");
String pname=rs.getString("PNAME");
// Print out the values
System.out.println(pno+"\t"+pname);
}
;
22-JDE
```

















EJBs				
<ul> <li>Enterprise Julie</li> <li>Part of Sun</li> <li>Goal:         <ul> <li>Ease develop based, applie</li> <li>Entity be</li> <li>Entity be</li> <li>Encanin an</li> <li>Session builded</li> <li>Encanin an</li> </ul> </li> <li>Benefits:         <ul> <li>Handles all t</li> </ul> </li> </ul>	ava Beans J2EE initiative oment of Web-oriented, 3-tien cations. can: osulates a persistent object th RDBMS oean: osulates transactions the crap for you (e.g., sessions	r, RDBMS- hat is mirrored s, connection		
<b>pooling</b> ,) 52 - JDBC	CSC309	20		